

- 100' Heavy Duty Spring Retractable Bonding
- To Ground Equipment Operating in
- Hazardous Atmospheres

Protection

Reinforced Steel

 Long Life Drive Spring •12/3 SJEOOW •125V

Hose Reels

RLCGA3100N

- Dissipates Static Electrical Buildup, Reducing Chances of Sparking & Potential for Explosion
- Industrial Grade Carbon Steel
  Guide Arm Adjusts
- Hi-Vis Orange Nylon Covered Cable, 1/8" O.D.
- 100 Amp Clamp Rating, 125° Max Temp

### CALL FOR PRICE

### RLCA58500LP

- 50' Premium Dutv
- Hose is Plumbed into Base
- Bent Tube Swivel Design
- Swivel is Nested Inside Spool
- <sup>1</sup>/<sub>2</sub>" x 50' Low-Pressure PVC Hose; Hose for Air or Water Service ONLY
- Base Plate & Upright Constructed from 14 Gauge Steel; Guide Arm is 13 Gauge & Spool is 16 Gauge Steel
- Reliable Speed Latch Allows for Positive Locking of Spool in 2 Positions per Rotation
- Individually Powder-Coated Steel Components
- Robotically Welded Steel Base
- Guide Arm Adjusts to 2 Positions 1/2" I.D. 300 psi

# **CALL FOR PRICE**

## **RLC811000LP**

- 100' Ultimate Duty Dual Pedestal
- Mounts to any Load-Bearing Surface
- 5-in-1, Heat Treated Aluminum Casting
- 2 Sealed Ball Bearings
- 3/8" x 100' Low-Pressure PVC Hose Included,
- Hose for Air or Water Service ONLY
- Versatile Reel Inlet can be Connected to Fluid Source on **Right or Left Side**
- Guide Arm Adjusts to 4 Different Positions
- Base Plate 7 Gauge Steel, Upright & Guide Arm 11 Gauge Steel, & Spool is 16 Gauge Steel
- <sup>3</sup>/<sub>8</sub>" I.D. 300 psi

### CALL FOR PRICE