



Wrench Sets

- Drop-Forged Alloy-Steel

V8T214 14-Pc SAE Angle

- 30° & 60° Angles Allow Use in 4 Different Positions
- Inc: $\frac{3}{8}$ ", $\frac{7}{16}$ ", $\frac{1}{2}$ ", $\frac{9}{16}$ ", $\frac{5}{8}$ ", $\frac{11}{16}$ ", $\frac{3}{4}$ ", $\frac{13}{16}$ ", $\frac{7}{8}$ ", $\frac{15}{16}$ ", 1", $\frac{11}{16}$ ", $\frac{1}{8}$ " & $\frac{1}{4}$ "

USER \$141.55 SRP **\$96.07**

V8T8308

8-Pc SAE Super-Thin

- Includes: $\frac{3}{8}$ " x $\frac{7}{16}$ ", $\frac{1}{2}$ " x $\frac{9}{16}$ ", $\frac{5}{8}$ " x $\frac{11}{16}$ ", $\frac{3}{4}$ " x $\frac{13}{16}$ ", $\frac{7}{8}$ " x $\frac{15}{16}$ ", 1" x $\frac{1}{16}$ ", $\frac{1}{8}$ " x $\frac{1}{4}$ " & $\frac{13}{16}$ " x $\frac{15}{16}$ "



USER \$83.98 SRP **\$56.96**



V8T8109

9-Pc Metric Super-Thin

- Includes: 8mm x 9mm, 10mm x 11mm, 12mm x 13mm, 14mm x 15mm, 16mm x 17mm, 18mm x 19mm, 20mm x 21mm, 24mm x 27mm, 30mm x 32mm

USER \$64.89 SRP **\$44.04**

V8T9215

15-Pc Jumbo SAE Service

- Use in Confined Spaces
- Drop-Forged Alloy Steel
- Includes: $\frac{3}{4}$ ", $\frac{13}{16}$ ", $\frac{7}{8}$ ", $\frac{15}{16}$ ", 1", $\frac{11}{16}$ ", $\frac{1}{8}$ ", $\frac{13}{16}$ ", $\frac{11}{4}$ ", $\frac{15}{16}$ ", $\frac{13}{8}$ ", $\frac{17}{16}$ ", $\frac{1}{2}$ ", $\frac{19}{16}$ ", $\frac{15}{8}$ "



USER \$252.50 SRP **\$171.21**

V8T3001

Dual Purpose Hose Cutter

- Cut Large Hoses up to 2 1/2" Diameter
- Mounting Holes Built In



USER \$134.02 SRP **\$91.05**

V8T3826

Mighty Worm Magnetic Pickup Tool

- 5mm Diameter Head Mounted on 30" Long Flexible Copper Wire
- Pick up more than 1/2 lb



USER \$10.26 SRP **\$6.96**

V8T3803

Clip-On Magnetic Dish

- Made of Strong Material
- Clips on Belt or Pocket • 3 Rare Earth Magnets



USER \$24.33 SRP **\$16.51**

SP40260

Universal Spring Compressor

- 2-Pc Internally Threaded Spring Compressor is a Great Option for MacPherson Strut, Coilover & other Accessible Springs
- 1" - 11" of Travel & 2645 lbf Max Working Load with 3x Safety Factor
- Vinyl Coated Ends, Safety Jaw & Ball Bearing Load Surface
- Use of both Hooks per Spring is Required



USER \$342.03 SRP **\$264.02**

SP86370

GM Van Cas/Cam Plate

- Front Adjustment Range: Camber/Caster +/- 1.50°
- Installation Time: 0.3 Hr/Side • Required: 1 Kit per Wheel
- Designed to be Adjusted with a $\frac{3}{8}$ " Drive Breaker Bar



USER \$8.20 SRP **\$6.33**



SP72210

1/4° Rear Half Shim for Chrysler

- Adjusts Camber or Toe

LTD QTY


SRP **\$20.12**

SP77938

Steering Wheel Holder

- Securely Holds Steering Wheel: Covered Hooks & Base Prevent Damage to Steering Wheel & Seat

THIS IS NOT A LOCKING DEVICE



USER \$128.64 SRP **\$99.30**

SP88810

W-Body Clamp Assembly

Remove or Install the Auxiliary Spring for Rear Spring or Strut Service



LTD QTY

SRP **\$97.74**

SP73167

SRP **\$13.19**

1" Hi Perf Lugnut Socket, CR-MO

LTD QTY




SP10010

Hose Cutter Tool

- Provides Straight, Even, Clean Cuts on Heater, Air Conditioning, Braided Rubber or Plastic Hose up to 1 1/8" Diameter



USER \$49.34 SRP **\$38.09**



SP10011 Replacement Blades

- High Grade Carbon Steel, 2 per Package

USER \$15.84 SRP **\$12.23**