

PC10 Series 30' Spring Driven Cord Reels INDOOR USE ONLY

- 20 Amps, 115 Volts 60 Hz Single Phase; 12/3 AWG SJO
- Non-Corrosive, High Strength CoxComposite™ Ratchet Hub with Self-Lubricating Bronze Bearings
- Solid 1-Piece, 12GA Steel Base & Support Post
- Compact & Lightweight Spring Driven Hose Reel
- CoxComposite™ Grommet with Continuous Radius Design
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish
- Adjustable Solid Rubber Cord Stop
- Sturdy Permanently Lubricated Precision Bearings
- 5' Lead Cable & Grounding Plug

CXPC10-3012-A

Single Industrial Receptacle

SRP **\$634.67**

CXPC10-3012-B

Quad "4 Plug" Industrial Receptacle

SRP **\$750.54**

Compact Hand Crank Hose Reels

ALL REELS SUPPLIED LESS HOSE

- Adjustable Tension Brake
- High Quality
 Steel Construction
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish



100 Series

- 4000 PSI
- Solid 1-Piece Heavy Gauge All Steel "U" Shaped Frame
- Machined Solid Brass 90° Full-Flow NPT Swivel
- Direct Hand Crank Rewind

CX112-3-100 100'3/8" ID, 5/8" OD

SRP **\$257.84**

CX117-3-250 250'3/8" ID, 5/8" OD

SRP **\$296.46**

1125 Series

- 3000 PSI
- 1-Piece All Welded 12 Gauge Steel "A" Frame Base
- Electroless Nickel Plated Steel 90° Full-Flow NPT Swivel Inlet
- Exclusive Low Profile Outlet Riser & Open Drum Slot Design
- Front Bevel Geared Crank Retraction

CX1125-5-100 100'3/4" ID, 11/4" OD

SRP \$490.61

CX1125-5-175 175'3/4" ID, 11/4" OD

SRP \$509.40

CXC-L350-5016-A

C "Combination" Air-Electric Series 50' Spring Driven Cord Reel

INDOOR USE ONLY

- ³/8" ID, 5/8" OD; 13 Amps, 300 Max PSI; 16/3 AWG 50' SJO
- 2 Reel Assembly for Dual Hose Applications, each Reel Operates Independently
- Machined from Solid Brass 90° Full-Flow NPT Swivel
- Lubricated & Enclosed Cartridge-Style Motor
- Precision Coil Spring Factory Tuned & Matched
- 1/4" Steel Base, Sturdy Single Expanded Pedestal Design
- Multi-Position Guide Arm, Adjusts to Wall, Floor & Overhead Positions
- Multi-Position Lock Ratchet Mechanism
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish
- Adjustable Solid Rubber Hose Stop
- Sturdy Permanently Lubricated Precision Bearings
- 5' Lead Cable & Grounding Plug
- Single Industrial Receptacle

SRP \$1,063.70



- Machined Solid Brass 90° Full-Flow NPT Swivel
- Lubricated & Enclosed Cartridge-Style Motor
- 1/4" Steel Base, Sturdy Single Pedestal
- Multi-Position Guide Arm
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish
- Adjustable Solid Rubber Hose Stop
- Sturdy Permanently Lubricated Precision Bearings

CXP-LP-150 1/4" ID 1/2" OD, 300 PSI

SRP **\$418.60**

CXP-LP-350 3/8" ID 5/8" OD, 300 PSI

SRP **\$460.35**

EZ-Coil Model

Controlled Retraction Speed up to 80% Slower

CXEZ-P-LP-350 3/8" ID 5/8" OD, 300 PSI

SRP \$548.04