



Wrench Sets

- Drop-Forged Alloy-Steel

V8T8308 8-Pc SAE Super-Thin

- Includes: $\frac{3}{8}$ " x $\frac{7}{16}$ ", $\frac{1}{2}$ " x $\frac{9}{16}$ ", $\frac{5}{8}$ " x $\frac{11}{16}$ ", $\frac{3}{4}$ " x $\frac{13}{16}$ ", $\frac{7}{8}$ " x $\frac{15}{16}$ ", 1" x $\frac{1}{6}$ ", $\frac{1}{8}$ " x $\frac{1}{4}$ " & $\frac{13}{16}$ " x $\frac{15}{16}$ "

USER \$83.98 SRP **\$56.96**



V8T8109

9-Pc Metric Super-Thin

- Includes: 8MM x 9MM, 10MM x 11MM, 12MM x 13MM, 14MM x 15MM, 16MM x 17MM, 18MM x 19MM, 20MM x 21MM, 24MM x 27MM, 30MM x 32MM

USER \$64.89 SRP **\$44.04**

V8T9215 15-Pc Jumbo SAE Service

- Use in Confined Spaces

- Includes: $\frac{3}{4}$ ", $\frac{13}{16}$ ", $\frac{7}{8}$ ", $\frac{15}{16}$ ", 1", $\frac{1}{16}$ ", $\frac{1}{8}$ ", $\frac{13}{16}$ ", $\frac{1}{4}$ ", $\frac{15}{16}$ ", $\frac{13}{8}$ ", $\frac{17}{16}$ ", $\frac{1}{2}$ ", $\frac{19}{16}$ ", $\frac{15}{8}$ "

USER \$252.50 SRP **\$171.21**



V8T7814

14-Pc $\frac{1}{2}$ " Dr Jumbo SAE Crowfoot

- Fully Polished

- Includes: $\frac{1}{16}$ ", $\frac{1}{8}$ ", $\frac{13}{16}$ ", $\frac{1}{4}$ ", $\frac{15}{16}$ ", $\frac{13}{8}$ ", $\frac{17}{16}$ ", $\frac{1}{2}$ ", $\frac{19}{16}$ ", $\frac{15}{8}$ ", 2" & Display Case

USER \$192.81 SRP **\$132.25**

V8T3001 Dual Purpose Hose Cutter

- Cut Large Hoses up to 2 $\frac{1}{2}$ " Diameter
- Mounting Holes Built In

USER \$134.02 SRP **\$91.05**



V8T3826 Mighty Worm Magnetic Pickup Tool

- 5mm Diameter Head Mounted on 30" Long Flexible Copper Wire
- Pick up more than $\frac{1}{2}$ LB

USER \$10.26 SRP **\$6.96**



V8T3803 Clip-On Magnetic Dish

- Made of Strong Material
- Clips on Belt or Pocket • 3 Rare Earth Magnets

USER \$24.33 SRP **\$16.51**



SP40260 Universal Spring Compressor

- 2-Pc Internally Threaded Spring Compressor is a Great Option for MacPherson Strut, Coilover & other Accessible Springs
- 1" - 11" of Travel & 2645 lbf Max Working Load with 3x Safety Factor
- Vinyl Coated Ends, Safety Jaw & Ball Bearing Load Surface
- Use of both Hooks per Spring is Required

USER \$342.03 SRP **\$264.02**



SP86370 GM Van Cas/Cam Plate

- Front Adjustment Range: Camber/Caster +/- 1.50°
- Installation Time: 0.3 Hr/Side • Required: 1 Kit per Wheel
- Designed to be Adjusted with a $\frac{3}{8}$ " Drive Breaker Bar

USER \$8.20 SRP **\$6.33**



SP72210

$\frac{1}{4}$ ° Rear Half Shim for Chrysler

- Adjusts Camber or Toe

LTD QTY


SRP **\$20.12**

SP77938 Steering Wheel Holder

- Securely Holds Steering Wheel: Covered Hooks & Base Prevent Damage to Steering Wheel & Seat

THIS IS NOT A LOCKING DEVICE

USER \$128.64 SRP **\$99.30**



SP88810 W-Body Clamp Assembly

Remove or Install the Auxiliary Spring for Rear Spring or Strut Service

SRP **\$97.74**




SP73167 SRP \$13.19 1" Hi Perf Lugnut Socket, CR-MO

LTD QTY

SP10010 Hose Cutter Tool

- Provides Straight, Even, Clean Cuts on Heater, Air Conditioning, Braided Rubber or Plastic Hose up to $\frac{1}{8}$ " Diameter

USER \$49.34 SRP **\$38.09**



SP10011 Replacement Blades

- High Grade Carbon Steel, 2 per Package

USER \$15.84 SRP **\$12.23**